

# DHI-XVR5108HS-4KL

## 8 Channel Penta-brid 4K Compact 1U Digital Video Recorder



- Embedded processor
- H.264+/H.264 video compression
- Support HDCVI/AHD/TVI/CVBS/IP video inputs
- Max 12 channels IP camera inputs, each channel up to 8MP; Max 48Mbps Incoming Bandwidth
- Smart Search and Intelligent Video System



### System Overview

Throughout the years, HDCVI technology gained international fame for becoming a brand new international standard for video surveillance, and has never stopped evolving. From 2MP to 4MP, now Dahua Technology brings HDCVI into the 4K era. It presents a much clear and vivid world.

As the perfect solution to upgrade existing video surveillance systems, XVR supports penta-brid access technology such as HDCVI, AHD, TVI, CVBS and IP to effortlessly integrate with popular industry formats, offering an affordable solution loaded with flexible options.

Designed as a full compatibility product, XVR is able to provide end user the simplicity of analog system, namely lower system cost, simple installation and use of existing cable. It is ideal for a wide range of applications such as public safety, retail store, transportation, home protection and education.

### Functions

#### Smart H.264+

Smart Codec, H.264+ can reduce up to 70% bit rate and storage requirements without having to invest in new cameras.

#### HDCVI/AHD/TVI/CVBS/IP Auto-detect

The XVR can auto recognize the signal of front-camera without any setting. It makes operation more friendly and convenient.

#### 8MP Resolution

The XVR supports up to 8MP HD resolution (3840 x 2160) HDCVI camera and IP camera input.

#### Coaxial Audio/Upgrade/Alarm

The integrated design can reduce wiring troubles which makes it much more cost-effective and convenient for installation..

### Intelligent Fan Design

The intelligent fan can automatically turn on or turn off according to the CPU temperature. This function can effectively reduce the fan noise to provide a better user experience while extending the life of the fan at the same time.

### Spot Output

It is made for a secondary monitor. This allows the operator to view one special monitor that assigned to selected cameras or video inputs from higher security areas.

### Intelligent Video System (IVS)

With built-in intelligent video analytics, the XVR has the ability to detect and analyze moving objects for improved video surveillance. The XVR provides optional standard intelligence at the edge allowing detection of multiple object behaviors such as abandoned or missing objects. IVS also supports Tripwire analytics, allowing the camera to detect when a pre-determined line has been crossed.

### Face Detection

It is a type technology being used in a variety of applications that search or identify individuals which show front cameras.

### Smart Search

This function helps you get more motion detect video during a short time through drawing a region when playback. It is very useful when an emergency occurs.

## Lite Series | DHI-XVR5108HS-4KL



Technical Specification		Video Detection and Alarm	
<b>System</b>		<b>Video Detection and Alarm</b>	
Main Processor	Embedded Processor	Trigger Events	Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Operating System	Embedded LINUX	Video Detection	Motion Detection, MD Zones: 396 (22 × 18), Video Loss, Tampering and Diagnosis
<b>Video and Audio</b>		Alarm input	N/A
Analog Camera Input	8 Channel, BNC	Relay Output	N/A
HDCVI Camera	4K, 4MP, 1080P@25/30fps, 720P@50/60fps, 720P@25/30fps	<b>Playback and Backup</b>	
AHD Camera	5MP, 4MP, 3MP, 1080P@25/30, 720P@25/30fps	Playback	1/4/9
TVI Camera	5MP, 3MP, 1080P@25/30, 720P@25/30fps	Search Mode	Time /Date, Alarm, MD and Exact Search (accurate to second)
CVBS Camera	PAL/NTSC	Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom
IP Camera Input	8+4 Channel, each channel up to 8MP	Backup Mode	USB Device/Network
Audio In/Out	1/1, RCA	<b>Storage</b>	
Two-way Talk	Reuse audio in/out, RCA	Internal HDD	1 SATA Port, up to 8TB capacity
<b>Recording</b>		eSATA	N/A
Compression	H.264+/H.264	<b>Auxiliary Interface</b>	
Resolution	4K, 5MP, 4MP, 3MP, 1080P, 720P, 960H, D1, CIF, QCIF	USB	2 USB Ports (1 USB 2.0, 1 USB 3.0)
Record Rate	Main stream: 4K(1~7fps); 5MP(1~12fps); 4MP/3MP(1~15fps); 1080P/720P/960H/D1/CIF/QCIF (1~25/30fps) Sub stream: 960H(1~15fps); D1/CIF/QCIF(1~25/30fps)	RS232	N/A
Bit Rate	1Kbps ~ 6144Kbps Per Channel	RS485	1 Port, for PTZ Control
Record Mode	Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop	<b>Electrical</b>	
Record Interval	1 ~ 60 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec	Power Supply	DC12V/2A
<b>Display</b>		Power Consumption	<10W (Without HDD)
Interface	1 HDMI, 1 VGA	<b>Construction</b>	
Resolution	HDMI: 3840×2160, 2560×1440, 1920×1080, 1280×1024, 1280×720, 1024×768 VGA: 1920×1080, 1280×1024, 1280×720, 1024×768	Dimensions	Compact 1U, 260×236×48mm(10.2"×9.3"×1.9")
Multi-screen Display	When IP extension mode not enabled: 1/4/8/9 When IP extension mode enabled: 1/4/8/9/16	Net Weight	0.75kg ( 1.7lb) (without HDD)
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording	Gross Weight	1.5kg (3.3lb)
<b>Network</b>		Installation	Desktop installation
Interface	1 RJ-45 Port (1000M)	<b>Environmental</b>	
Network Function	HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search (Support Dahua IP camera, DVR, NVS, etc.)	Operating Conditions	-10°C ~ +55°C (+14°F ~ +131°F), 0~ 90% RH
Max. User Access	128 users	Storage Conditions	-20°C ~ +70°C (-4°F ~ +158°F), 0~ 90% RH
Smart Phone	iPhone, iPad, Android	<b>Third-party Support</b>	
Interoperability	ONVIF 2.42, CGI Conformant	Third-party Support	Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek, and more
		<b>Certifications</b>	
		Certifications	FCC: Part 15 Subpart B CE: CE-LVD: EN 60950-1/IEC 60950-1 CE-EMC: EN 61000-3-2, EN 61000-3-3, EN 55032, EN 50130, EN 55024 UL: UL 60950-1

## Lite Series | DHI-XVR5108HS-4KL

### Ordering Information


Type	Part Number	Description
8 Channel XVR	DHI-XVR5108HS-4KL	8 Channel Penta-brid 4K Compact 1U Digital Video Recorder

### Dimensions (mm)



### Rear Panel

DHI-XVR5108HS-4KL



- |   |                          |   |                    |
|---|--------------------------|---|--------------------|
| 1 | VIDEO IN                 | 6 | RS485 Interface    |
| 2 | AUDIO IN, RCA Connector  | 7 | USB Interface      |
| 3 | AUDIO OUT, RCA Connector | 8 | DC 12V Power Input |
| 4 | HDMI Interface           | 9 | VGA Interface      |
| 5 | Network Interface        |   |                    |